

PFEIFER

www.PFEIFER-BAUMASCHINEN.com

Helmut Jakob Pfeifer
Baumaschinen - Nutzfahrzeuge

Am Flutgraben 4 (Steinbacherstraße 49, dann rechts)
D - 64658 Fürth (Bergstraße)

Tel: +49 (0) 6253 807 770

Fax: +49 (0) 6253 807 900

E-Mail: office@pfeifer-baumaschinen.com



JCB 526 - 55 TURBO 4x4x4 - 5.5m / 2.6t.

Gelände - Teleskoparmstapler JCB, Typ: **526 - 55 TURBO 4x4x4**, Ersteinsatz: 2006, **HUBKRAFT: 2.600 kg**, **HUBHÖHE: 5.50 m**, 4-Zylinder **TURBO-Diesel Motor** (101.3 PS / 74.5 kW bei 2.200 U/min), **LANGE LADEGABELN** (Gabellänge: 1.200 mm, Breite Gabelaufnahme: 1.320 mm) - **MANITOU-AUFNAHME**, **HYDRAULISCHER SCHNELLWECHSLER**, **ALLRAD** und **ALLRADLENKUNG** (4x4x4) - **HUNDEGAN**, **ZUSATZHYDRAULIK** (2 Anschlüsse), **ÜBERLAST-WARNEINRICHTUNG**, **ROPS / FOPS**, **DACHSCHUTZGITTER**, Anhängerkupplung, großes Führerhaus (Colorglas) – Kabinenhöhe nur 2.320 mm, **ARBEITSSCHEINWERFER** (vorne / hinten), Verkehrsbeleuchtung, Komfortsitz, Scheibenwischer, Außenspiegel, Heizung / Lüftung, Halte- und Transportösen. Bereifung: **IMPLEMENT BKT** (160 / 70 – 20) – rundum ca. 95 %. Transportmaße: Länge: 6.180 mm (ca. 4.880 mm ohne Gabeln), Breite: 2.250 mm, Höhe: 2.320 mm. *** **FINANZIERUNG MÖGLICH / TRANSPORT GÜNSTIG (WELTWEIT) / BEI EXPORT IST NUR DER NETTOPREIS ZU BEZAHLEN (!)** *** © pb ----- Rough terrain telescopic forklift JCB, type: **526 - 55 TURBO 4x4x4**, first use: 2006, **LIFTING FORCE: 2.600 kg**, **LIFTING HEIGHT: 5.50 m**, 4-cylinder **TURBO-diesel engine** (101.3 PS / 74.5 kW at 2.200 rpm), **LONG FORKS** (forks length: 1.200 mm, forks admission width: approx. 1.320 mm) - **MANITOU-ADMISSION**, **HYDRAULICAL QUICK CHANGER**, **4-WHEEL-DRIVE-SYSTEM** and **ALL-WHEEL-STEERING** (4x4x4) – **CRAB STEERING** (dogway), **ADDITIONAL HYDRAULIC** (2 connection), **OVERLOAD-PROTECTION-SYSTEM**, **ROPS / FOPS**, **PROTECTION ROOF**, follower coupling, big driverhouse (colourglasses) – cabine height only 2.320 mm, **WORKING FLOODLIGHT** (in front / behind), road lightings, comfortseat, windshield wipers, back view mirrors, heating / ventilation, hold-and transporthooks. Tyres: **IMPLEMENT BKT** (160 / 70 – 20). Transport dimensions: see above. *** **EQUIPMENT IS FINANCEABLE** in nearly all european countries / **TRANSPORTATION WORLDWIDE POSSIBLE** at good conditions / **EXPORT: ONLY THE NET AMOUNT NEED TO PAID (!)** *** © pb



www.PFEIFER-BAUMASCHINEN.de